

## Single plug-in bridge - PLC-BP A1-14 - 2980283


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Passive feed-through bridge; can be plugged in instead of a relay or a solid-state relay, bridges terminal points A1 and 14



### Key Commercial Data

|                                      |   |
|--------------------------------------|---|
| Packing unit                         | 1 STK   |
| Minimum order quantity               | 10 STK  |
| GTIN                                 | <br>4 017918 729981 |
| GTIN                                 | 4017918729981   |
| Weight per Piece (excluding packing) | 4.810 g   |
| Custom tariff number                 | 85389099  |
| Country of origin                    | Germany   |

### Technical data

#### Dimensions

|        |       |
|--------|-------|
| Width  | 5 mm  |
| Height | 28 mm |
| Depth  | 15 mm |

#### General

|                       |            |
|-----------------------|------------|
| Nominal voltage $U_N$ | 60 V AC/DC |
| Color                 | black      |

#### Environmental Product Compliance

|            |  |
|------------|--|
| China RoHS | Environmentally Friendly Use Period = 50 |
|------------|--|

## Single plug-in bridge - PLC-BP A1-14 - 2980283

### Technical data

#### Environmental Product Compliance

|  |   |
|--|---|
|  | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |
|--|---|