



Rev.	Descrizione	Approvata da	Data

ROLLON EMORE engineering		Materiale	Stato materiale	Dimensioni del grezzo	Peso Kg.																												
<table border="1"> <thead> <tr> <th colspan="2">LINEAR</th> <th colspan="2">ANGULAR</th> </tr> </thead> <tbody> <tr> <td>0.5-6</td> <td>± 0.05</td> <td>0-10</td> <td>± 1°</td> </tr> <tr> <td>6-30</td> <td>± 0.1</td> <td>10-50</td> <td>± 0°30'</td> </tr> <tr> <td>30-120</td> <td>± 0.15</td> <td>50-120</td> <td>± 0°20'</td> </tr> <tr> <td>120-400</td> <td>± 0.2</td> <td>120-400</td> <td>± 0°10'</td> </tr> <tr> <td>400-1000</td> <td>± 0.3</td> <td>400-</td> <td>± 0°5'</td> </tr> <tr> <td>1000-2000</td> <td>± 0.5</td> <td></td> <td></td> </tr> </tbody> </table>		LINEAR		ANGULAR		0.5-6	± 0.05	0-10	± 1°	6-30	± 0.1	10-50	± 0°30'	30-120	± 0.15	50-120	± 0°20'	120-400	± 0.2	120-400	± 0°10'	400-1000	± 0.3	400-	± 0°5'	1000-2000	± 0.5			Trattamento	Sostituisce il	Sostituito da	
LINEAR		ANGULAR																															
0.5-6	± 0.05	0-10	± 1°																														
6-30	± 0.1	10-50	± 0°30'																														
30-120	± 0.15	50-120	± 0°20'																														
120-400	± 0.2	120-400	± 0°10'																														
400-1000	± 0.3	400-	± 0°5'																														
1000-2000	± 0.5																																
<table border="1"> <thead> <tr> <th colspan="4">GEOMETRIC</th> </tr> </thead> <tbody> <tr> <td>0-10</td> <td>0.02</td> <td>0-100</td> <td>0.2</td> </tr> <tr> <td>10-30</td> <td>0.05</td> <td>100-300</td> <td>0.3</td> </tr> <tr> <td>30-100</td> <td>0.1</td> <td>300-1000</td> <td>0.4</td> </tr> <tr> <td>100-300</td> <td>0.2</td> <td>1000-3000</td> <td>0.5</td> </tr> <tr> <td>300-1000</td> <td>0.3</td> <td></td> <td></td> </tr> <tr> <td>1000-3000</td> <td>0.4</td> <td></td> <td></td> </tr> </tbody> </table>		GEOMETRIC				0-10	0.02	0-100	0.2	10-30	0.05	100-300	0.3	30-100	0.1	300-1000	0.4	100-300	0.2	1000-3000	0.5	300-1000	0.3			1000-3000	0.4			Disegnato da A.Cassani	Data 21-03-2013	Descrizione Unità lineare Robot 220 CU=6600 spec.	
GEOMETRIC																																	
0-10	0.02	0-100	0.2																														
10-30	0.05	100-300	0.3																														
30-100	0.1	300-1000	0.4																														
100-300	0.2	1000-3000	0.5																														
300-1000	0.3																																
1000-3000	0.4																																
<table border="1"> <thead> <tr> <th colspan="2">GENERAL TOLERANCE ISO 2768-H</th> </tr> </thead> <tbody> <tr> <td>□</td> <td>0-10 0.02</td> </tr> <tr> <td>□</td> <td>10-30 0.05</td> </tr> <tr> <td>□</td> <td>30-100 0.1</td> </tr> <tr> <td>□</td> <td>100-300 0.2</td> </tr> <tr> <td>□</td> <td>300-1000 0.3</td> </tr> <tr> <td>□</td> <td>1000-3000 0.4</td> </tr> </tbody> </table>		GENERAL TOLERANCE ISO 2768-H		□	0-10 0.02	□	10-30 0.05	□	30-100 0.1	□	100-300 0.2	□	300-1000 0.3	□	1000-3000 0.4	Formato A3	Scala 1:100	Foglio 1 di 1															
GENERAL TOLERANCE ISO 2768-H																																	
□	0-10 0.02																																
□	10-30 0.05																																
□	30-100 0.1																																
□	100-300 0.2																																
□	300-1000 0.3																																
□	1000-3000 0.4																																
<table border="1"> <thead> <tr> <th colspan="2">CHAMFER SHARP EDGES 0.5x0.2x45°</th> </tr> </thead> <tbody> <tr> <td>⊕</td> <td>0.1</td> </tr> <tr> <td>⊕</td> <td>0-3000 0.5</td> </tr> </tbody> </table>		CHAMFER SHARP EDGES 0.5x0.2x45°		⊕	0.1	⊕	0-3000 0.5			EL.MORE Srl si riserva a termine di legge la proprietà di questo disegno con divieto di riprodurlo o diffonderlo senza la sua autorizzazione.																							
CHAMFER SHARP EDGES 0.5x0.2x45°																																	
⊕	0.1																																
⊕	0-3000 0.5																																
Codice R224E095701AS01		Rev.																															